


NOTES:

- 4 3/4 MTG HOLES
- * APPROX. DIM.-DO NOT USE FOR PRE-FABRICATION OF CONNECTING PIPING.
- UNIT NO.'S 420 THRU 600 HAVE TWO FAN MOTORS AND THREE FANS.

UNIT NO.	APPROX. WEIGHT		L	H	C	R
	SHIPPING	OPERATING				
PMC-560	29,710	31,790	18' 1/8"	14' 7-3/4"	69-3/4"	47-7/8"

Revised: 10/23/80
Revised: 2/13/80



CERTIFIED FOR: _____
 CUSTOMER'S ORDER NO.: _____ EVAPCO NO.: A 802167
 CAPACITY: 311 T.R. NH₃ REFRIG. 95 °COND. 20 °SUCT. 81 °W.B.
 FAN MOTOR (1) 15 & (1) 7 1/2 H.P. ELEC. SPEC. 460/60/3
two speed, single winding
 PUMP MOTOR _____ H.P. ELEC. SPEC. _____
 REMARKS Less pump for remote sump application. To include
bottom screens. Left hand unit.

EVAPCO, INC.
 3120 Frederick Avenue
 Baltimore, Maryland
 21229
 Telephone (301) 945-3400
 clb